

260407-contenu des tables OSM dans OSM-raw

```
debian@vps-02c1f983-vps-ovh-net:~$ docker exec -i alteris_postgis psql -U alteris_admin -d alteris_geo -c "\d osm_raw.buildings"
```

Table "osm_raw.buildings"				
Column	Type	Collation	Nullable	Default
osm_id	bigint			
access	text			
addr:housename	text			
addr:housenumber	text			
addr:interpolation	text			
admin_level	text			
aerialway	text			
aeroway	text			
amenity	text			
area	text			
barrier	text			
bicycle	text			
brand	text			
bridge	text			
boundary	text			
building	text			
construction	text			
covered	text			
culvert	text			
cutting	text			
denomination	text			
disused	text			
embankment	text			
foot	text			
generator:source	text			
harbour	text			
highway	text			
historic	text			
horse	text			
intermittent	text			

junction	text			
landuse	text			
layer	text			
leisure	text			
lock	text			
man_made	text			
military	text			
motorcar	text			
name	text			
natural	text			
office	text			
oneway	text			
operator	text			
place	text			
population	text			
power	text			
power_source	text			
public_transport	text			
railway	text			
ref	text			
religion	text			
route	text			
service	text			
shop	text			
sport	text			
surface	text			
toll	text			
tourism	text			
tower:type	text			
tracktype	text			
tunnel	text			
water	text			
waterway	text			
wetland	text			
width	text			
wood	text			
z_order	integer			
way_area	real			
tags	hstore			
way	geometry(Geometry,3857)			

Indexes:

"planet_osm_polygon_osm_id_idx" btree (osm_id)

"planet_osm_polygon_way_idx" gist (way)

Triggers:

planet_osm_polygon_osm2pgsql_valid BEFORE INSERT OR UPDATE ON osm_raw.buildings FOR EACH ROW EXECUTE FUNCTION planet_osm_polygon_osm2pgsql_valid()

debian@vps-02c1f983-vps-ovh-net:~\$

Revision #1

Created 2026-04-10 09:15:16 UTC by Julien

Updated 2026-04-10 09:15:16 UTC by Julien